INSPECTION CHECKLISTS

CALIFORNIA STATE UNIVERSITY SACRAMENTO

The following checklist is a guide. It may be used in its entirety or be modified to the specific user's needs by adding or subtracting items from the checklist. For questions concerning any item, contact the Office of Environmental Health and Safety.

(40)	STAIRS	& ST	AIRW	YAYS
------	---------------	------	------	-------------

Name:	Date :					
Location of Inspection:						
1. Are standard stair rails or handrails on all stairways having four or more risers?	Yes 🗆 No 🗆	Comments:				
2. Are all stairways at least 22 inches wide?	Yes 🗆 No 🗆	Comments:				
3. Do stairs have at least a 6'6'' overhead clearance?	Yes 🗆 No 🗆	Comments:				
4. Do stairs angle no more than 50 and no less than 30 degrees?	Yes 🗌 No 🗌	Comments:				
5. Are stairs of hollow-pan type treads and landings filled to noising level with solid material?	Yes 🗌 No 🗌	Comments:				
6. Are step risers on stairs uniform from top to bottom, with no riser spacing greater than 7-1/2 inches?	Yes 🗌 No 🗌	Comments:				
7. Are steps on stairs and stairways designed or provided with a surface that renders them slip resistant?	Yes 🗌 No 🗌	Comments:				
8. Are stairway handrails located between 30 and 34 inches above the leading edge of stair treads?	Yes No	Comments:				

9. Do stairway handrails have a least 1-1/2 inches of clearance between the handrails and the wall or surface they are mounted on?	Yes 🗆	No 🗆	Comments:
10. Are stairway handrails capable of withstanding a load of 200 pounds, applied in any direction?	Yes 🗆	No 🗆	Comments:
11. Where stairs or stairways exit directly into any area where vehicles may be operated, are adequate barriers and warnings provided to prevent employees stepping into the path of traffic?	Yes 🗆	No 🗆	Comments:
12. Do stairway landings have a dimension measured in the direction of travel, at least equal to width of the stairway?	Yes 🗆	No 🗌	Comments:
13. Is the vertical distance between stairway landings limited to 12 feet or less?	Yes 🗆	No 🗌	Comments: